



```
root@localhost:~# cat /etc/default/grub
GRUB_TIMEOUT=5
GRUB_DEFAULT=saved
GRUB_DISABLE_SUBMENU=true
GRUB_TERMINAL_OUTPUT="console"
GRUB_CMDLINE_LINUX="rd.lvm.lv=centos/root rd.lvm.lv=centos/swap crashkernel=auto
rhgb quiet rootflags=usrquota,grpquota"
GRUB_DISABLE_RECOVERY="true"
```

```
root@localhost:~# mount | grep ' / '
/dev/mapper/centos-root on / type xfs (rw,relatime,seclabel,attr2,inode64,noquota)
root@localhost:~# mount | grep ' / '
/dev/mapper/centos-root on / type xfs (rw,relatime,seclabel,attr2,inode64,noquota)
root@localhost:~# vi /etc/default/grub
root@localhost:~# vi /etc/default/grub
root@localhost:~# cp /boot/grub2/grub.cfg /boot/grub2/grub.cfg.orig
root@localhost:~# grub2-mkconfig -o /boot/grub2/grub.cfg
Generating grub configuration file ...
Found linux image: /boot/vmlinuz-3.10.0-229.el7.x86_64
Found initrd image: /boot/initramfs-3.10.0-229.el7.x86_64.img
Found linux image: /boot/vmlinuz-0-rescue-deee8f22093f4344becff562a5f78c46
Found initrd image: /boot/initramfs-0-rescue-deee8f22093f4344becff562a5f78c46.img
done
root@localhost:~#
```

```
- root@ ~ 21:21:55 - root@localhost:~
Last login: Fri Jul 15 12:49:20 2016 from 192.168.1.17
[root@localhost ~]# mount | grep ' / '
/dev/mapper/centos-root on / type xfs (rw,relatime,seclabel,attr2,inode64,usrqu
ta,grpquota)
[root@localhost ~]#
```